

NW-8300-(1/2/4 Zone) FIRE ALARM CONTROL PANEL

- Zone numbers: 1-4 zones
- AC input: 110V~220V
- Battery type: 2x12V/7AH
- Max number of devices per zone: 20pcs
- End of line resistor:4.7 k Ω
- DC output: 29V
- Alarm output: Relay output
- Max siren output current: 2x500mA@24VDC(nominal)
- Operating temperature: -10°C~50°C
- Operating humidity: \leq 95%RH(no condensation)
- Dimension: L400*W105*H350mm



NW-8300-(8/16/32 Zone) FIRE ALARM CONTROL PANEL

- Zone numbers: 1-32 zones
- AC input: 110V~220V
- Battery type: 2x12V/7AH
- Max number of devices per zone: 20pcs
- End of line resistor:4.7 k Ω
- DC output: 29V
- Alarm output: Relay output
- Max siren output current: 4x500mA@24VDC(nominal)
- Operating temperature: -10°C~50°C
- Operating humidity: \leq 95%RH(no condensation)
- Dimension: L400*W105*H350mm



CE ISO 9001

CONTACT US

061-789-1469

Grand Elite Supplies

SD-602

WIRED PHOTOELECTRIC SMOKE DETECTOR

- Operating voltage: DC 9V~35V
- Standby current: 2 WIRE: $\leq 50\mu\text{A}$
4 WIRE: $\leq 50\mu\text{A}(\text{relay NO})/\leq 16\text{mA}(\text{relay NC})$
- Alarm current: 2 WIRE: 20~50mA@12V/40~50mA@24V
4 WIRE: $\leq 40\text{mA}(\text{relay NO})/\leq \text{mA}(\text{relay NC})$
- Sensitivity: 0.08-0.16dB/m
- Alarm indication: Red LED
- Operating temperature: 0°C~50°C
- Operating humidity: $\leq 95\%RH$ (no condensation)
- Material: ABS
- Standard: EN54-7:2008
- Certificate: CE, RoHS
- Dimension: 103*H53mm
- 2 wire or wire optional



SD-607

WIRED SMOKE DETECTOR

- Operating voltage: DC 9V~35V
- Standby current: $\leq 50\mu\text{A}$
- Alarm current: 40~50mA@24V
- Sensitivity: 0.08-0.16dB/m
- Alarm indication: Red LED
- Reset: Power off
- Alarm output: Remote led for 2 wires
- Contact rating N/A for 2 wires
- Operating temperature: 0°C~50°C
- Operating humidity: $\leq 95\%RH$ (no condensation)
- Material: ABS
- Standard: EN54-7:2008
- Certificate: CE
- Dimension: 98.5*H47.8mm

CE ISO 9001

CONTACT US

061-789-1469

Grand Elite Supplies

HD-502 WIRED HEAT DETECTOR

- Operating voltage: DC 9V~35V
- Standby current: 2 WIRE: $\leq 50\mu\text{A}$
4 WIRE: $\leq 50\mu\text{A}(\text{relay NO})/\leq 16\text{mA}(\text{relay NC})$
- Alarm current: 2 WIRE: 20~50mA@12V/40~50mA@24V
4 WIRE: $\leq 40\text{mA}(\text{relay NO})/\leq \text{mA}(\text{relay NC})$
- Temp. trip point: 57°C
- Alarm indication: Red LED
- Operating temperature: -10°C~50°C
- Operating humidity: $\leq 95\%RH$ (no condensation)
- Material: ABS
- Standard: EN54-5:2008
- Certificate: CE
- Dimension: 100.7*H50.7mm
- 2 wire or 4 wire optional



HD-503 WIRED HEAT DETECTOR

- Operating voltage: DC 9V~35V
- Standby current: 2 wire: $\leq 50\mu\text{A}$
4 wire: $\leq 50\mu\text{A}(\text{Relay NO})/\leq 16\text{mA}(\text{relay NC})$
- Alarm current: 2 wire: 20~25mA@12V/40~50mA@24V
4 wire: $\leq 40\text{mA}(\text{relay NO})/\leq 20\text{mA}(\text{relay NC})$
- Temp. trip point: 57°C
- Alarm indication: Red LED
- Operating temperature: -10°C~50°C
- Operating humidity: $\leq 95\%RH$ (no condensation)
- Material: ABS
- Standard: EN54-5:2008
- Certificate: CE
- Dimension: 101*H55mm
- 2 wire or 4 wire optional

HD-507 WIRED HEAT DETECTOR

- Operating voltage: DC 9V~35V
- Standby current: $\leq 50\mu\text{A}$
- Alarm current: 40~50mA@24V
- Temp. trip point: 57°C
- Alarm indication: Red LED
- Reset: Power off
- Alarm output: Remote led for 2 wires
- Contact rating N/A for 2 wires
- Operating temperature: -10°C~50°C
- Operating humidity: $\leq 95\%RH$ (no condensation)
- Material: ABS
- Standard: EN54-7:2008
- Certificate: CE
- Dimension: 98.5*H47.8mm



CE ISO 9001

CONTACT US


061-789-1469

Grand Elite Supplies

FA-507

RESETTABLE FIRE CALL POINT

- Operating voltage: DC 9~28V
- Max. current: 45mA at 24V DC
- Contact resistance: $\leq 0.2\text{ohm}$
- Operating temperature: -10°C - 50°C
- Operating humidity: 10~93RH(no condensation)
- Material: ABS
- Color: Red
- Dimension: L140*W104*H45mm



FA-400

FIRE ALARM BELL

- Operating voltage: DC 24V/AC 220V
- Working current: $\leq 50 \text{ mA}$
- Audio alarm: $\geq 95\text{dB}$ / $\geq 97 \text{ dB}$
- Driving way: Motor
- Base material: Aluminum or plastic
- Base size: 6" / 8"
- Dimension: 150mm / 200mm

CE ISO 9001

CONTACT US

061-789-1469

Grand Elite Supplies

FA-410L

FIRE STROBE SOUNDER

- Operating voltage: DC 6~24V
- Working current: 10~30mA@12V ; 20~50mA@24V
- Alarm sound pressure: $\geq 103\text{dB@12V}$; $\geq 105\text{dB@24V}$
- Flash intensity: $\geq 1.2\text{Ws}$, flash period: $\leq 1\text{s}$
- Flash light: LED or Tube
 - LED life: ≥ 100000 times
 - Tube life: ≥ 40000 times
- Provenience of sound alarm: I Ambulance sound
 - II Sound of police car
 - III Sound of fire engine
- Operating temperature: $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$
- Operating humidity: $\leq 95\%\text{RH}$ (no condensation)
- Material: ABS
- Dimension: L125*W125* H50mm



FA-414

FIRE STROBE SOUNDER

- Operating voltage: DC 12~24V
- Alarm current: $\leq 60\text{mA}$
- Flash Period: 120 times/min
- Alarm sound pressure: $\geq 105\text{dB}$
- Shell Material: Hard plastics shell
- Operating temperature: $-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$
- Operating humidity: $\leq 95\%\text{RH}$ (no condensation)
- Material: ABS
- Color: Red
- Dimension: L128.3*W122*H104.6mm



CE ISO 9001

CONTACT US

061-789-1469

Grand Elite Supplies